



ECOLOG-PRO Base


- Preinstalled software
- Up to 50 measurement points



TECHNICAL SPECIFICATIONS ECOLOG-PRO BASE

ECOLOG-PRO Base

The ECOLOG-PRO Base is the «heart» of the ECOLOG Plug&Play solution for connected monitoring for rooms and equipment. All of the required software is already installed on a PC, which is designed for ultimate reliability. The comprehensive compatibility with the time-tested ECOLOG-NET data loggers and the new ECOLOG-PRO modules allows for a great deal of flexibility.



Configuration example: warehouse

High-bay racking and cold storage room, both to be monitored with ECOLOG-NET data loggers, extended with ECOLOG-PRO modules for monitoring an additional cold storage room with local alarming:
28 measurement points

High-bay racking:

- 2 × ECOLOG-NET LR8
- 2 × RTH1i
- 12 × RT1e

Cold storage room:

- 1 × ECOLOG-PRO LBR
- 3 × 4PT
- 1 × 4DO



we prove it.



- All-in-one, calibrated and validated system results in lowest TCO
- Compatible with ECOLOG-NET and the powerful new ECOLOG-PRO data loggers
- User-friendly web application and sensor-based configuration

Technical Specifications ECOLOG-PRO Base

| | |
|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU | Intel® Core™ i3-7101TE 3.4 GHz |
| Memory | 4 GB DDR4 SO-DIMM |
| Hard disk | 120 GB SSD |
| Maximum number of measurement points | 50 |
| Memory capacity | Measurement values of 50 measurement points for 18 month |
| Data logger compatibility | ECOLOG-NET, ECOLOG-PRO |
| Interfaces | 1 × USB 3.0 to connect external data storage for backups and updates 1 × RJ45 WLAN module 2.4 GHz and 5 GHz with 2 antennas |
| Power supply | 19 V, integrated UPS for controlled shutdown in the event of a power outage |
| Operating system | Windows 10 LTSB |
| Environmental operating temperature / humidity | 0 °C..+40 °C 10 %RH..95 %RH, noncondensing |
| Case dimensions weight | SECC steel 282 × 201 × 56 mm (11.10 × 7.91 × 2.20 inch) 3 kg (105.82 oz) |
| Installed software | elproMONITOR elproUSER elproEVENT ECOLOG-PRO Base Maintenance elproMONITOR WebAccess Note: In order to use WebAccess, the elproLOG MONITOR-WebAccess web application must be installed on a separate web server. elproLOG MONITOR-WebAccess can be downloaded from the Client Area. The license is included in the software maintenance agreement. |
| ECOLOG-PRO modules | The ECOLOG-PRO Base is compatible with following modules: ECOLOG-PRO - Communication module: LBR - MODBUS modules: 4PT, 4MA, 2TH, 4DI, 4DO ECOLOG-NET - Data loggers: LP4, LA8, LR8 - Radio sensors: RT1e, RT2e, RTH1i, RTH1e, RA2e |